



Motor 1962 connected to rotator 1960 is labeled in red. This is supported in the specification on page 67 lines 27 to page 68 line 2:

"The rotator 1960 includes stops so that the trays will essentially be flipped through 180°. A rotator motor 1962 is used to drive the rotator. The rotator motor can also have stops or be a motor that works between 0° and 180°."

No new matter is added.

RECEIVED
FEB 06 2001
TO 3600 MAIL ROOM

IN THE SPECIFICATION

On page 42 line 1, please change "flipper 2000" to --flipper 1900--. This is supported on page 55 line 28-page 56 line 1 ("The tray inverter 1900 may also be called the flipper.") No new matter is added.

IN THE CLAIMS

Please amend claims 1, 3, 9, 12, 13, 14, 17, 18, 19 and 22 and add new claims 26-31 as follows (all claims are reprinted here):

1. ~~[Amended Once] A machine-vision system for inspecting a device, the device having a first side and a second side, the machine-vision system comprising:~~

~~a first inspection station for inspecting a first side of a device;
a second inspection station for inspecting a second side of a device; and
a tray-transfer device that operates to move the device from the first inspection station to the second inspection station, said tray-transfer device further including an inverting mechanism that operates to invert the device so that the first [second] side of the device can be inspected at the first inspection station and the second side of the device can be inspected at the second inspection station.~~

2. ~~The system of claim 1 wherein the inverting mechanism is positioned between the first inspection position and the second inspection position.~~

3. [Amended Once] [The machine-vision system of claim 1]

A machine-vision system for inspecting a device, the device having a first side and a second side, the machine-vision system comprising:

a first inspection station for inspecting a first side of a device;

a second inspection station for inspecting a second side of a device; and

a tray-transfer device that operates to move the device from the first inspection station to the second inspection station, said tray-transfer device further including an inverting mechanism that operates to invert the device so that the first second side of the device can be inspected at the first inspection station and the second side of the device can be inspected at the second inspection station, wherein the inverting mechanism further comprises a mechanism for flipping the devices carried in a tray, the mechanism further comprising:

a first jaw having a surface for receiving a first tray;

a second jaw having a surface for receiving a second tray;

a mover for moving the first jaw, the first tray having a plurality of devices, the second tray, and the second jaw into engagement with each other, said first tray associated with the first jaw and the second tray associated with the second jaw; and

a rotator for rotating the first and second [jaw] jaws.

4. ¹ The machine-vision system of claim 3 wherein the mover moves the first jaw in a direction substantially perpendicular to the surface for receiving a tray associated with the first jaw.

5. ¹ The machine-vision system of claim 3 wherein the mover moves the first jaw and the second jaw in a direction substantially perpendicular to the surface for receiving a tray associated with the first jaw.

6. [Amended Once] ¹ The machine-vision system of claim 3 wherein the inverting mechanism moves the plurality of devices to the second tray such that the second sides of [a] the plurality of devices are presented for inspection.

c1
Q3 2
7. [Amended Once] The machine-vision system of claim 1 wherein the rotator of the inverting mechanism moves the plurality of devices to the second tray such that the second sides of [a] the plurality of devices are presented for inspection.

7
8. The machine-vision system of claim 6 wherein the mover of the inverting mechanism is adapted to place the plurality of devices in the second tray at the second inspection station.

Q4
9. [Amended Once] The machine-vision system of claim 7 wherein the tray transfer device includes means for moving the second inspection station with respect to the inverting [mechanism] mechanism.

8
10. The machine-vision system of claim 7 further comprising a picker for picking devices which fail inspection from the second tray.

c1
Q5
11. [Amended Once] A machine-vision system for inspecting a plurality of devices positioned within a plurality of device-carrying trays, the machine-vision system comprising:
a first tray adapted to carry a plurality of devices;
a second tray adapted to carry a plurality of devices;
a flip station for flipping the plurality of devices carried in [a] the first tray from a first inspection position in the first tray to a second inspection position in the second tray.

10
12. [Amended Once] [The machine-vision system of claim 11]

A machine-vision system for inspecting a plurality of devices positioned within a plurality of device-carrying trays, the machine-vision system comprising:

a first tray adapted to carry a plurality of devices;
a second tray adapted to carry a plurality of devices;
a flip station for flipping the plurality of devices carried in a first tray from a first inspection position in the first tray to a second inspection position in the second tray wherein the flip station further comprises:

a first jaw having a surface for receiving a first tray;

83

A

a second jaw having a surface for receiving a tray;
a mover for moving the first jaw, a first tray having a plurality of devices,
a second tray, and the second jaw into engagement with each other, said first tray
associated with the first jaw and the second tray associated with the second jaw;
and
a rotator for rotating the first and second [jaw] jaws.

c2
13. [Amended Once] The machine-vision system of claim ¹⁰12 further comprising:
a first [slide clamp] ~~tray-transfer device~~ for holding at least the first tray, said first [slide
clamp] ~~tray-transfer device~~ moving the first tray from [a] the first inspection station to [a] the flip
station; and
a second [slide clamp] ~~tray-transfer device~~ for holding at least the second tray, said
second [slide clamp] ~~tray-transfer device~~ moving the second tray from the flip station to the
second inspection station.

14. [Amended Once] The machine-vision system of claim [11] ¹⁰12 wherein the flip
station further comprises a mechanism for flipping the devices carried in a tray, the mechanism
further comprising means for limiting the motion of the rotator.

c2
15. The machine-vision system of claim ¹⁰12 wherein the mover moves the first jaw in a
direction substantially perpendicular to the surface for receiving a tray associated with the first
jaw.

¹²16. The machine-vision system of claim ¹⁰12 wherein the mover moves the first jaw and the
second jaw in a direction substantially perpendicular to the surface for receiving a tray associated
with the first jaw.

c2 16
17. [Amended Once] A flipping mechanism for transferring a plurality of devices from a
position in a first tray to a position in a second tray, the flipping mechanism comprising:
a first jaw having a surface adapted to receive the first tray;

84

C2
a second jaw having a surface adapted to receive the second tray;
a mover for moving the first jaw, the first tray, the second tray, and the second jaw into engagement with each other, said first tray associated with the first jaw and the second tray associated with the second jaw; and
a rotator for rotating the first and second [jaw] jaws.

OK 16
18. [Amended Once] The [machine-vision system] flipping mechanism of claim 17 wherein the mover can be controlled to remove the first tray from a first inspection surface.

16
19. [Amended Once] The [machine-vision system] flipping mechanism of claim 17 wherein the mover can be controlled to place the second tray at a second inspection surface.

20. A method for acquiring physical information associated with a plurality of devices placed in a tray, the method comprising the steps of:
inspecting a first side of a device within a first tray;
removing the first tray from a first surface and placing the first tray at a flip station;
moving a second tray to a position near the first tray;
flipping the first tray and second tray to move the device from the first tray to the second tray and place the device in the second tray so that a second side of the device is presented in the second tray; and
inspecting a second side of the device within the second tray.

21. The method of claim 20, further including the step of moving the second tray to a second inspection surface.

C2 23
OK 22. [Amended Once] A machine-vision system for inspecting a plurality of devices and for inverting the plurality of devices from being positioned in a first tray, the machine-vision system comprising:

a first jaw having a surface for receiving the first tray;
a second jaw having a surface;

85 A

c2
an
a mover for moving the first jaw, the first tray having a plurality of devices, and the second jaw into engagement with each other, said first tray associated with the first jaw; and a rotator for rotating the first and second [jaw] jaws.

c2
23
23. The machine-vision system of claim 22 further comprising;
a first conveyer for moving the first tray having a plurality of devices therein to the first jaw; and
a second conveyer for moving the first tray having a plurality of devices therein from the first jaw.

24. The machine-vision system of claim 22 wherein the first jaw is capable of holding, in any position, a tray devoid of devices.

25. The machine-vision system of claim 22 further comprising;
a slider for transferring the inverted devices from the second jaw into the first tray.

c1
26. [New] ~~The machine-vision system of claim 1 wherein the flip station further comprises a mechanism for flipping the devices while the devices are carried in a tray.~~

27. [New] The machine-vision system of claim 3 wherein the rotator rotates the first and second jaws simultaneously.

28. [New] The machine-vision system of claim 10 wherein the rotator rotates the first and second jaws simultaneously.

29. [New] The flipping mechanism of claim 14 wherein the rotator rotates the first and second jaws simultaneously.

30. [New] The method of claim 20, wherein moving the second tray to the position near the first tray further includes moving the second tray to engage the first tray, and wherein flipping

86

A

AMENDMENT AND RESPONSE UNDER 37 CFR § 1.111

Serial Number: 09/350,251

Filing Date: July 8, 1999

Title: TRAY FLIPPER AND METHOD FOR PARTS INSPECTION

Page 8

Dkt: 139.059US1

C3
the first tray and second tray is done simultaneously after engagement.

CA 27 23
31. [New] The machine-vision system of claim 22 wherein the rotator rotates the first and second jaws simultaneously.

87

D